W-S 10/14/22 Brine-to-water heat pump




KEY FEATURES

- Inverter technology and Scroll compressor
- Ability to modulate thermal power (12.5-100%) and the speed of the production circulator (20-100%)
- Compact installations: circulation pumps, safety valves and expansion vessels of the primary and seconday circuits inbuilt. 3-way valve for DHW production integrated
- Active cooling inbuilt (VOLTA W-S-A and W-S-F) Passive cooling inbuilt (VOLTA W-S-P and W-S-F)


- Integrated energy meters
- Simultaneous heating and cooling production allowing unique performance
- SUPERHEATER: Allows DHW production up to 70°C without the need of an electrical heater
- Ground source or hybrid collection systems: management of modulating air source units
- Internet connection and remote control
- Hybridisation with photovoltaic enery inbuilt













COLLECTION







Air



Hubrid

SERVICES



DHW











Heating Active/Passive Cooling

Pool

Photovoltaic

Internet

RANGE

1-10kW VOLTA W-S 10 VOLTA W-S 14 3-14kW 5-22kW VOLTA W-S 22







CASCADE









W-S Datasheet



- Inverter technology and Scroll compressor
- Power ranges: 1-10 kW / 3-14 kW / 5-22 kW
- Domestic hot water production with external tank
- Heating and pool production
- Active cooling production inbuilt
- Passive cooling production inbuilt (free cooling)
- Internet connection and control remote
- Photovoltaic hybridisation integrated
- Superheater for DHW production up to 70°C and for simultaneous DHW and heating/cooling
- Integrated cascade control of up to 3 units
- Single-phase (230V) or three-phase (400V) power supply

VOLTA W-S-H	VOLTA W-S-P	VOLTA W-S-A	VOLTA W-S-F
• DHW	• DHW	• DHW	• DHW
Heating	Heating	Heating	Heating
	 Passive cooling 	Active cooling	Passive cooling
			Active cooling



UK Distributors of Heat Pumps and Air Conditioning Systems

www.essaircon.com 0845 880 5862 sales@essaircon.com environmental-site-supplies-ltd-